

AMENDMENT

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Canceled)
2. (Canceled)
3. (Canceled)
4. (Canceled)
5. (Canceled)
6. (Canceled)
7. (Canceled)
8. (Previously Presented) A dual-position gun sling, comprising:
 - a first gun sling with a padded portion at an upper end;
 - a second gun sling with a padded portion at an upper end;
 - means on each of said first and second gun slings to engage an upper gun swivel;
 - a Y-strap for said first and second gun slings to engage a lower gun swivel, said Y-strap comprising:
 - a first clip for engaging a first strap at a first end to engage said lower gun swivel;
 - a second strap attached at a first end to a central portion of said first strap; and
 - said first and second straps having end clips at respective second ends to engage

said first and second gun slings,

wherein said end clips provide a length adjustment means for said first and second gun slings, a first side of an attachment means is located on said padded portion of said first gun sling, and a second side of an attachment means is located on said padded portion of said second gun sling to selectively engage said first side of said attachment means.

9. (Canceled)

10. (Previously presented) The dual-position gun sling of claim 8, wherein said attachment means is at least one means selected from the group consisting of snaps, hook-and-loop fasteners, magnetic fasteners, button-and-hole fasteners, zippers, locking plastic strips, and clasp-type fasteners.

11. (Previously presented) The dual-position gun sling of claim 8, wherein said means on each of said first and second gun slings to engage an upper gun swivel is selected from the group consisting of a single clip for engaging an end portion of each of said first and second gun slings, a single triangular loop at said upper swivel and clips for engaging said first and second gun slings, and a single plate with first and second slots at said upper swivel and clips for engaging said first and second gun slings.

12. (Previously presented) A method of using a Y-strap to allow the use of two gun slings on a single gun, comprising:

engaging a first clip located at a first end of a first strap of said Y-strap to a lower swivel on said gun;

wherein a second strap is attached at a first end to a central portion of said first strap so as to form said Y-strap;

engaging end clips at respective second ends of said first and second straps to one end of said two gun slings; and

engaging a second end of said two gun slings to an upper swivel on said gun.